

- Available in .010 x 54" Roll Length: 100 Ft.
- Printable with Solvent, latex & UV Printers
- Full-Bleed Printing
- Easy Kiss-Cut or Contour Cut
- Bright White Point Washable Surface
- Excellent for Short Term Floor Applications

- ★ Safety Tested Anti-Slip ASTM D-2047
- ★ Fire Rated ASTM E-84
- ★ No Lamination Required
- ★ Excellent Scratch Resistance
- ★ Tough and Durable



LOW-TAC

To be used with Solvent, UV & Latex Inks

Designed for Smooth Indoor Surfaces

- Wooden Platforms
- Metal
- Plastic Laminate or Linoleum
- Tile & Carpeting



HIGH-TAC

To be used with Solvent, UV & Latex Inks

Designed for Smooth Outdoor Surfaces

- Paving Stone
- Concrete or Cement
- Untreated Natural Stone
- Certain types of Brick
- Plush/Shag Carpeting



HIGH-TAC EX

To be used with Solvent, UV & Latex Inks

Designed for Rough Outdoor Surfaces

- Aging Concrete
- Asphalt
- Brick

Contact us Today to Place your Order! (310) 608-1115

PVC TECH | 1931 E. Vista Bella Way Dominguez Hills, CA 90220 | www.pvctech.com