



Non Top Coated Static Cling Material

## Tested & Ranked #1 in Highest Clarity Films on the Market!

Clarity and			SULL:
Highly Clear	.006	x 51" · 55"	
e /	.008	x 36.75" · 40" · 51" · 54" · 60.5" x 51.5"	Available in 300 yd. Rolls
White	.008	x 51.5" · 54" · 54.5" · Custom 60"	
+ 1	Digito	ıl Ready! 50 yds. = 150 l	-t. Rolls
esion d pility Excel	lent for	: POP Displays · Protective Masking Window Decals	g · Signage ·
Ad	heres to	o smooth, clean and glossy surface Glass, Metal and Plastics.	s such as:
If Sto	oring:		
	1	Store in a dry and clean, air-conditioned envir at 70-72° F/ 20-22° C and 50% Relative Hu	
		Lay on flat surface.	
		Do not stack excessively.	
		Do NOT expose to extreme heat, cold or to humidity.	
nks	Poor	storage and temperature conditions will affect Resulting in hazing, printing or adhesion prol	

## (310) 608-1115 info@pvctech.com

www.pvctech.com ©PVC TECH. All Rights Reserved. This release is for informational purposes only and does not constitute a guarantee or warranty, express or implied. The information contained herein is true and accurate to the best of our knowledge as advised by our manufacturer. It is the customer's responsibility to determine the suitability of this product for the customer's intended use, and PVC tech Corp does not assume any liability for the customer's use of this product or the information contained herein.